

LED CUSEC Pendelleuchte

- › direkt/indirekt strahlend
- › Acrylabdeckung in opal
- › aus scharfkantig gezogenem Aluminiumprofil
- › Oberfläche pulverbeschichtet

- › LED in SMD-Technologie,
2-Step MacAdam, L80/B10 – 50000 h

- › Low Flux LED-Typ 13
- › Mid Flux LED-Typ 14
- › High Flux LED-Typ 15



opal, direkt/indirekt

H 40			
	B 150	L 590	
H 100			
	B 150	L 870	
H 100			
	B 150	L 1150	
H 100			
	B 150	L 1430	
H 100			
	B 150	L 1710	

Lichtstrom High Efficiency (CRI > 82)

Artikel	LED-Typ	3000 K	4000 K	Leistung
95712	13	2000 lm	2070 lm	18 W
	14	2800 lm	2900 lm	24 W
	15	3970 lm	4120 lm	34 W
95713	13	3000 lm	3110 lm	26 W
	14	4200 lm	4360 lm	35 W
	15	5950 lm	6190 lm	49 W
95714	13	4000 lm	4150 lm	33 W
	14	5600 lm	5810 lm	45 W
	15	7940 lm	8250 lm	65 W
95715	13	5000 lm	5190 lm	40 W
	14	7000 lm	7260 lm	56 W
	15	9920 lm	10310 lm	80 W
95716	13	6000 lm	6220 lm	48 W
	14	8400 lm	8720 lm	66 W
	15	11910 lm	12380 lm	95 W